



A-T Controls, Inc.

9955 International Blvd. • Cincinnati, Ohio 45246
Phone: 513.247.5465 Fax: 513.247.5462
www.atcontrols.com

Engineer: NPM No.: TR0090

Date Created: 10/07/2015

Date Modified:

SIZE	150# POWER SEAL FLOW COEFFICIENT (CV)										
	5°	10°	20°	30°	40°	50°	60°	70°	80°	85°	90°
2"	1	2	6	13	23	36	50	74	92	101	105
2.5"	1	3	9	19	35	54	77	112	141	154	160
3"	1	4	12	25	46	71	101	147	185	202	210
4"	2	9	26	53	97	150	211	308	387	422	440
6"	5	18	52	108	198	306	432	630	792	864	900
8"	10	38	110	228	418	646	912	1,330	1,672	1,824	1,900
10"	16	62	180	372	682	1,054	1,488	2,170	2,728	2,976	3,100
12"	24	94	273	564	1,034	1,598	2,256	3,290	4,136	4,512	4,700
14"	31	122	354	732	1,342	2,074	2,928	4,270	5,368	5,856	6,100
16"	41	162	470	972	1,782	2,754	3,888	5,670	7,128	7,776	8,100
18"	54	216	626	1,296	2,376	3,672	5,184	7,560	9,504	10,368	10,800
20"	69	274	795	1,644	3,014	4,658	6,576	9,590	12,056	13,152	13,700
24"	105	420	1,218	2,520	4,620	7,140	10,080	14,700	18,480	20,160	21,000



Manual and Automated Quarter Turn Valves
Complete Valve and Damper Automation

