



WIRE COLOR CODING

BLUE ——— N.O.
 BLACK ——— N.C.
 VIOLET ——— COM.

MODEL NO.	ADJUSTABLE RANGE	
	psi	bar
10-C10	4 TO 50	0.3 TO 3.4
10-C11	10 TO 150	0.7 TO 10.3
10-C12	30 TO 600	2.1 TO 41.0

FACTORY SEALED LEADWIRES 20±1" LG.

1/2 NPT (ALUMINUM)

CAUTION LABEL

ADJUSTMENT ACCESS COVER, SLIDE UP TO OPEN.

SLOTTED ADJUSTMENT SCREW, TURN IN TO RAISE SET POINT.

SPECIFICATIONS:

UL RECOGNIZED, CSA CERTIFIED
 E/R: 5 AMPS 250 VAC

4 1/16" [103.2mm]

1/8 NPT (BRASS)

SYM	DESCRIPTION	DATE	DWN	APPD
K	CHANGED kPa TO bar. ECN#E0044	10-23-02	S.R.	H.N.
J	REDRAWN, REV. RANGES PER ECN#C5565	5-10-96	P.W.	L.K.
REVISIONS				

ORIGINAL DATE 2-26-91
DRWN PETER WEILER
CHKD A. BARTER
APPD L. KHATCHADORIAN
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

TITLE
 10-C
 SERIES
 <DIAPHRAGM>



UNITED ELECTRIC
 CONTROLS COMPANY
 WATERTOWN * MASSACHUSETTS

DF001D

DWG NO
 A-12858

DO NOT SCALE THIS DRAWING

SCALE FULL