




# VARIABLE AREA FLUOROPOLYMER FLOWMETERS

In-Line,  $\pm 5\%$  Accuracy, Chemically Inert, In-Line



Connection	A	B
1/4"	5-11/16" [144]	1-1/4" [31.8]
3/8"	5-11/16" [144]	1-1/4" [31.8]
1/2"	10-1/2" [267]	2" [50.8]
3/4"	10-1/2" [267]	2" [50.8]

Constructed entirely of Fluoropolymers, the **SERIES VAT** Flowmeters are ideal for high purity or corrosive liquid applications. Flowmeters feature a 0 to 10 scale for flow indication. Each unit is individually leak tested to a leak integrity rating of  $1 \times 10^{-7}$  sccs helium or better. The Series VAT are designed for in-line mounting and include a removable protective shield.

MODEL CHART			
Model		Low Range	
With Valve	Without Valve	Connections	Flow Rate GPH (ml/min)
VAT-311	VAT-301	1/4" female NPT	1.98 (125)
VAT-312	VAT-302	1/4" female NPT	3.91 (250)
VAT-313	VAT-303	1/4" female NPT	6.34 (400)
VAT-314	VAT-304	1/4" female NPT	7.92 (500)
VAT-315	VAT-305	1/4" female NPT	15.85 (1000)
VAT-316	VAT-306	3/8" female NPT	31.69 (2000)
VAT-317	VAT-307	3/8" female NPT	39.62 (2500)
VAT-318	VAT-308	3/8" female NPT	47.54 (3000)
VAT-319	VAT-309	3/8" female NPT	79.23 (5000)

OPTION	
Use order code:	Description
NISTCAL-FL1	NIST traceable calibration certificate

## SPECIFICATIONS

**Service:** Compatible liquids.

**Wetted Materials:** Flowtube: PFA; Float and end fittings: PTFE; Guide rods: PCTFE.

**Temperature Limit:** 250°F (121°C).

**Pressure Limit:** 100 psig (6.9 bar).

**Accuracy:**  $\pm 5\%$  FS @ 70°F (21.1°C) and 14.7 psia (1 atm absolute).

**Process Connections:** See chart.

**Leak Integrity:**  $1 \times 10^{-7}$  sccs of helium.

**Scale:** 0 to 10 markings.

**Mounting:** Vertical, in-line.

MODEL CHART			
Model		High Range	
With Valve	Without Valve	Connections	Flow Rate GPM (L/min)
VAT-6110	VAT-6010	1/2" female NPT	3.43 (13)
VAT-6111	VAT-6011	1/2" female NPT	5.28 (20)
VAT-6112	VAT-6012	3/4" female NPT	7.93 (30)
VAT-6113	VAT-6013	3/4" female NPT	10.57 (40)
VAT-6114	VAT-6014	3/4" female NPT	11.89 (45)