

CT6 Pump



CT6: Designed for Transferring Virtually All Crop Protection Products

Highest Flow Rates for Faster Loading

Features and Benefits:

- · Market-leading flow rates
- Complete "out of the box" pumping systems
- · Self-priming from a dry state
- Multiple configurations for use with caged IBCs, mini bulk tanks and drums
- · Easy to service





Pumps Designed for Compatibility With the Entire Range of Crop Chemical Formulations

Options

- Flow rates up to 13 gpm (CT6) or 18 gpm (CT6 HF)
- · Voltages: 12 volt and 115 volt
- Multiple configurations:
 - CES CT6 side mount for use with 275-gallon or 330-gallon caged IBCs with bottom outlet
 - CT6 Caddy pump in protective frame for use with caged IBCs, mini bulk tanks or drums
 - CES CT6 span cap horizontal mount for use with mini bulk tanks with 9-in opening
 - CT6 vertical mount for use with drums or tank lid with 2-in opening
 - CT6-MM vertical mount integrated with Micro Matic® three-pin coupler for use with drums or tanks fitted with Micro Matic three-pin container valve and suction tube
- Hoses available in standard EPDM with optional cross-linked poly liner







Bulletin PSS-90-20.24a (E) March 2015. © 2015 Flowserve Corporation.

To find your local Flowserve representative:

For more information about Flowserve Corporation, visit www.flowserve.com or call +1 937 890 5839.

Flowserve Corporation

Scienco Pumps 3732 Cook Blvd. Suite 101 Chesapeake, Virginia 22323 USA Telephone: 1 800 343 PUMP (7867)

USA and Canada

Flowserve Corporation 5215 North O'Connor Blvd. Suite 2300 Irving, Texas 75039-5421 USA Telephone: +1 937 890 5839

Europe, Middle East, Africa

Flowserve Corporation Parallelweg 13 4878 AH Etten-Leur The Netherlands Telephone: +31 76 502 8100

Latin America

Flowserve Corporation
Martín Rodriguez 4460
B1644CGN-Victoria-San Fernando
Buenos Aires, Argentina
Telephone: +54 11 4006 8700
Telefax: +54 11 4714 1610